

Auxiliaries

RZ - AX710 Adhesion Promoter

Product Description

Additives used to increase adhesion power of Reiz basecoat or Topcoat on metal substrates.
Optional for 1K/2K primer.

Technical Characteristics

Color: light yellow Shelf life: 24 months at 25°C

Pre-treatment

See process described in **TDS of Reiz Basecoat or Topcoat** - Solid Basecoat 2c, Metallic Colors 2c, Red Pearl 2c, Xirallic / Pearlescent Basecoat 3c, Solid Topcoat.

Mixing Ratio Application Drying	Stir well before use. Option 1: When spraying basecoat/topcoat directly to metal substrates without epoxy and putty: Add 10 - 20% of RZ - AX710 to 1 liter of Reiz original basecoat or topcoat. Prepare the paint for application by adding hardener or thinner as indicated in the TDS of the topcoat/clearcoat being adjusted. g mers directly metal subs es (e.g. iron, stainless steel, galvanized um with t epoxy a or putty: d 10 0% of - AX710 to 1 r of Rei iginal 1K/2K primer. pare pain or applicatio y addi ardener or thinner as indicated in the TDS of 1K/2K ime ste Strain before application. As specified in the TDS of the products in which RZ - AX710 is being used. As specified in the TDS of the products in which RZ - AX710 is being used.
--	---

The products are suitable for professional use only. The data contained in this publication are based on our current knowledge and experience.
You can obtain the latest version of technical data sheet from our website at www.wonder-global.com or directly from your supplier.